

KYDEX® RING

MODEL LVKYR



DESCRIPTION:

KYDEX® rings are used to correct mis-cut or oversized holes in ceilings and as a backing material behind sprinkler canopies. When ceiling tiles are being replaced, the hole that is cut in the ceiling to accommodate the sprinkler and escutcheon is often larger than the original. Use of the KYDEX® ring also allows replacement of ceiling tiles without the removal of most types of sprinkler canopies.

INSTALLATION:

KYDEX® rings are installed as a backing material behind existing or new sprinkler canopies. When installing with a new installation, slip the KYDEX® ring over the sprinkler then install sprinkler/canopy assembly. The KYDEX® ring will be held in place when the sprinkler canopy has been adjusted to meet the ceiling material. For existing applications, cut the KYDEX® ring, then twist the cut area apart and slip behind the existing sprinkler head/canopy assembly. Scissors should be used for cutting the KYDEX® material.

FEATURES:

- **Materials:** 0.28" KYDEX® T
- **Fire rating:** UL 94
- **Color:** white
- **Available sizes:** 4.0" OD x 1-3/4" ID
4.0" OD x 2" ID
- **Packaging:** 100/poly bag

PROJECT	APPROVAL STAMP
PROJECT:	<input type="checkbox"/> APPROVED
ADDRESS:	<input type="checkbox"/> APPROVED AS NOTED
ENGINEER:	<input type="checkbox"/> NOT APPROVED
SUBMITTAL DATA:	REMARKS:
NOTES 1:	
NOTES 2:	