

## TEST & DRAIN PRV KIT

## MODEL LVTDPR








## **FEATURES**:

- Tamper Resistant 5.6k test orifice & sight glass
- Field adjustable 175 310 psi pressure relief valve
- Pre-assembled for field installation saving time & money!
- Available in 1", 1-1/4", 1-1/2", 2"
- 300 PSI rated Lansdale UL/FM Approved Test & Drain

MATERIAL LIST		
ITEM	DESCRIPTION	
1	½" x 175-310 PSI Pressure Relief Valve	
2	S x S x ½" Galv. MI Tee	
3	S x CL Galv. Nipple	
4	Lansdale Test & Drain	
5	3/8" Reinforced PVC Tubing	
6	½" <b>x</b> <sup>3</sup> ⁄ <sub>8</sub> " 90 ° Brass Elbow	
7	S x ½" X S Galv. MITee	
8	³⅓" Hose Clamp	

\*Note: S stands for size of Test & Drain



DIMENSIONS			
SIZE (IN)	L (IN)		
1"	10 1/8		
1 1/4"	111/8		
1 ½"	11 <sup>5</sup> ⁄8		
2"	115%		

PROJECT	APPROVAL STAMP
PROJECT:	☐ APPROVED
ADDRESS:	☐ APPROVED AS NOTED
ENGINEER:	☐ NOT APPROVED
SUBMITTAL DATA:	REMARKS:
NOTES 1:	
NOTES 2:	